



## Main

Product	Double Throw Safety Switch
Duty Rating	General duty
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Number of Poles	4
Current Rating	400 A
Voltage Rating	600 V AC 600 V DC
Enclosure Rating	NEMA 3R
Motor power hp	125 Hp at 240 V AC 50-60 Hz for 3 phase motors 250 Hp at 480 V AC 50-60 Hz for 3 phase motors 350 Hp at 600 V AC 50-60 Hz for 3 phase motors 50 hp at 250 V DC

## Complementary

Short-circuit current	10 KA H or K 100 kA R, J or T
Fuse type	H or K R, J or T
Mounting Type	Surface
Wire Size	AWG 1/0...750 kcmil aluminium/copper
Tightening torque	550 Lbf.in (62.14 N.m) 0.08...0.47 in <sup>2</sup> (53.49...304 mm <sup>2</sup> ) (AWG 1/0...750 kcmil) 62.14 lbf.in (7.02 N.m) 0.08...0.24 in <sup>2</sup> (53.49...152 mm <sup>2</sup> ) (2 x AWG 1/0...2 x 300 kcmil)
Depth	8.88 in (225.55 mm)
Width	28.40 in (721.36 mm)
Height	64.20 in (1630.68 mm)
Net Weight	220.46 lb(US) (100 kg)

## Environment

Certifications	UL Listed
----------------	-----------

## Ordering and shipping details

Category	00133-DT SWITCH,NEMA3R
Discount Schedule	DE1
GTIN	3606481716804
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	64.21 in (163.1 cm)
Package 1 Width	28.39 in (72.1 cm)
Package 1 Length	8.90 in (22.6 cm)
Package 1 Weight	220.00 lb(US) (99.79 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations