

CH365AWKEI2

Safety switch, heavy duty, fusible, 400A, 600 VAC/VDC, 3 poles, 350 hp, NEMA 12, interlock 2NO/NC



Main

Range of product	Square D
Product or component type	Single Throw Safety Switch
Line Rated Current	400 A
NEMA degree of protection	NEMA 3R/12 galvanized steel
Maximum Horse Power Rating	100 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 250 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 125 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 350 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 50 Hp 250 V DC 50 hp at 600 V DC
Disconnecter device type	Fusible disconnect
Maximum short-circuit current	200 KA 10 kA
Device mounting	Surface
Number of poles	3
Phase	3 phase
Product certifications	CSA
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Wiring configuration	4-wire

Complementary

Maximum Width	26.25 in (666.75 mm)
Height	46.25 in (1174.75 mm)
Depth	10.13 in (257.30 mm)
Tightening torque	550 lbf.in (62.14 N.m) AWG 1/0...750 kcmil)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.