

Product Datasheet

Characteristic

XMLK150P2D23

pressure sensor XMLK - 0..150psi - 1/
4NPT - 4..20mA - M12 - set of 1



Main

range of product	OsiSense XM
product or component type	electronic pressure sensors
pressure sensor type	pressure transmitter
pressure sensor name	XMLK
electrical circuit type	control circuit
pressure sensor size	150 bar
local display	without
controlled fluid	air 32...176 °F (0...80 °C) fresh water 32...176 °F (0...80 °C)
fluid connection type	1/4" - 18 NPT (male)
electrical connection	1 male connector M12, 4 pins
[Us] rated supply voltage	24 V DC SELV, voltage limits: 8...33 V
current consumption	< 20 mA
type of output signal	analogue
analogue output function	4...20 mA, 2-wire
quantity per set	set of 1
type of packing	individual

Complementary

pressure setting range	0...150 psi
maximum permissible accidental pressure	300 psi
destruction pressure	450 psi
materials in contact with fluid	ceramic nitrile (NBR) stainless steel type AISI 303
operating position	any position
protection type	load short-circuit reverse polarity
electromagnetic compatibility	electrostatic discharge immunity test conforming to EN/IEC 61000-4-2 - test level 8 kV air, 6 kV contact susceptibility to electromagnetic fields conforming to EN/IEC 61000-4-3 - test level 10 V/m (f = 80...1000 MHz) electrical fast transient/burst immunity test conforming to EN/IEC 61000-4-4 - test level 2 kV 1.2/50 µs shock waves immunity test conforming to EN/IEC 61000-4-5 - test level 500 V 12 Ohm, 1 kV 42 Ohm radiated RF fields conforming to EN/IEC 61000-4-6 - test level 10 V (f

	= 0.15...80 MHz) immunity to magnetic fields conforming to EN/IEC 61000-4-8 - test level 30 A/m (f = 50 Hz)
[Uimp] rated impulse withstand voltage	0.5 kV
response time on output	< 5 ms
measurement accuracy	+/- 1 % of the measuring range
accuracy	0.1 % of the measuring range
drift of the sensitivity	+/- 0.04 % of measuring range/°K
drift of the zero point	+/- 0.03 % of measuring range/°K
repeat accuracy	+/- 1 % of the measuring range
mechanical durability	>= 10000000 cycles
product weight	0.24 lb(US) (0.11 kg)
diameter	1.42 in (36 mm)
length	2.58 in (65.5 mm)
scale type	fixed differential

Environment

standards	CE EN/IEC 61326-2-3
product certifications	UL 508 RCM CSA C22.2 No 14 EAC
protective treatment	TC
ambient air temperature for operation	32...176 °F (0...80 °C)
ambient air temperature for storage	-13...176 °F (-25...80 °C)
vibration resistance	20 gn (f = 9...2000 Hz) conforming to EN/IEC 60068-2-6
shock resistance	25 gn 11 ms conforming to EN/IEC 60068-2-27
IP degree of protection	IP65 conforming to EN/IEC 60529
NEMA degree of protection	NEMA 4

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold