



# WIRE TERMINATION

## Covers

- Helps prevent contact with live terminals



No. of Circuits	For Use with			
	89-200 Clear Cat. No.	89-300 Clear Cat. No.	89-400 Clear Cat. No.	89-500 Clear Cat. No.
2	<b>89-233</b>	<b>89-334</b>	<b>89-434</b>	—
4	<b>89-235</b>	<b>89-335</b>	<b>89-435</b>	<b>89-514</b>
6	<b>89-236</b>	<b>89-336</b>	<b>89-436</b>	<b>89-516</b>
8	<b>89-237</b>	—	<b>89-437</b>	<b>89-518</b>
10	<b>89-238</b>	<b>89-338</b>	<b>89-438</b>	—
12	<b>89-239</b>	<b>89-339</b>	<b>89-439</b>	<b>89-520</b>

## Quick Connects

- Allows fast, flexible circuit changes

For Use with Terminal Strip Series	Tab Size (Inches)	Qty.	Flat - None Cat. No.	Flat - Flat Cat. No.
89-300	.187 x .020	10	<b>89-314</b>	<b>89-317</b>
89-200 & 89-400	.250 x .031	10	<b>89-414</b>	<b>89-417</b>

## Jumpers

- Provides easy connection of multiple circuits

For Use with Terminal Strip Series	Center Spacing (In.)	Quantity	Flat Slip-on Cat. No.	Over Barrier Slip-on Cat. No.	Flat 12-Circuit Cat. No.
89-200	.562	10	 <b>89-229</b>	 <b>89-224</b>	—
		100	<b>89-230</b>	—	—
89-300	.375	10	<b>89-323</b>	<b>89-324</b>	—
		100	<b>89-330</b>	—	—
89-400	.437	10	<b>89-423</b>	<b>89-424</b>	—
		100	<b>89-430</b>	—	—
89-500	.625	2	—	—	<b>89-525</b>

## Barrier Strips

- Recessed screws and tubular contacts provide added safety and help prevent short circuits
- Tubular contacts connect stripped, un-terminated solid or stranded wire directly to each contact
- Integrated wire protectors prevent twisting and breakage of stranded wire during connection
- Modular 12-circuit design can be cut into smaller sections, or stacked end-to-end
- Rugged nylon construction, UL 94V2
- Operating temperature rated to 105°C (221°F)



Electrical Ratings	Wire Range	No. of Circuits	Torque in.-lb.	Model No.	Cat. No.
20A/300V UL	22 - 12 AWG	12	3.5	PA8DS	<b>89-608</b>
10A/400V CSA	20 - 18 AWG				
30A/300V UL	22 - 10 AWG	12	4.4	PA10DS	<b>89-610</b>
20A/400V CSA	18 - 14 AWG				
35A/300V UL/CUL	22 - 10 AWG	12	7.0	PA12DS	<b>89-612</b>
50A/300V UL/CUL	20 - 8 AWG	12	12.0	PA14DS	<b>89-614</b>