

Wall-Mounted Single LGX Bracket

Description

This wall-mountable bracket, designed for patching purposes, accommodates 1 LGX module. It is an excellent alternative to the 1-strip wall-mount when space is limited and only simple patching is needed. Its simplicity and flexibility allow for Flat Drop Cassettes, Distribution Modules or Cassettes, Adapter Strips, MUX and DeMUX modules and any other LGX footprint module to be installed with ease when space is limited.

Features and Benefits

Compatible with both copper and fiber products with standard LGX footprint
Wall mountable with standard wood screws
Excellent alternative to the 1 strip wall mount

Ideal for Main Point of Entry (MPOE) or closets with limited space
Up to 24 fibers (using LC connectors) or 6 Keystone modules

Applications

Entrance facility
Telecommunications room
Equipment room

Consolidation point
Central office
Cellular tower base station

Certification and Compliance

TIA-569
UL 94
RoHS

Commercial Building Standard for Telecommunications Pathways and Spaces.
Tests for Flammability of Plastic Material for Parts in Devices and Appliances
Directive on Restriction of Hazardous Substances



Part Number

CP-005258

Description

Wall-mounted Single LGX Bracket

Packaging

1 unit per bag

Physical Characteristics

Parameter	Value
Fiber count capacity	24 fibers maximum
UTP cable capacity	6 ports maximum
Panel material	16 Gauge cold rolled steel (CRS)
Panel finish	Black Sandex
Overall dimensions	146.6 mm (5.77 in) x 38.1 mm (1.50 in) x 35.1 mm (1.38 in)

Mechanical Characteristics

Parameter	Value
Installation temperature	-25° C (-13° F) ~ 40° C (104° F)
Storage temperature	-25° C (-13° F) ~ 55° C (131° F)
Relative humidity	≤ 85% (30° C)

Related Products

- Drop Cassette
- LGX Strips (Copper or Fiber)
- 3 LGX 1U Patch Panel
- 4U LGX Wall Mount

