

# Technical Information Bulletin

## LED Linear



Date:	_____	Name of distributor:	_____
In hands date of project:	_____	Client #:	_____
Project name/Number:	_____	Name of end user:	_____

### ORDERING INFORMATION

**Order code:** 67161  
**Description:** T5/25W/850/46/BYP/277-347/ND/STD  
**UPC:** 69549671614  
**Case quantity:** 25  
**DLC Unique ID:** PLQUT5INUU2F



Nominal length : 46 in. (1 168 mm) Dia. : 19/16 in. (21 mm)

### PHYSICAL DATA

**Shape:** T5  
**Base:** G5  
**Material:** Glass

### PERFORMANCE DATA

**Install method:** Ballast bypass  
**Lamp Watts (W):** 25  
**Volts (VAC):** 277-347  
**Colour temperature (K)<sup>1</sup>:** 5 000  
**Initial Lumens (lm)<sup>2</sup>:** 3 400  
**Initial lumens per watt (lm/W):** 136  
**Life L70 (hrs):** 50 000  
**CRI:** 82  
**Operating temperature range:** -25°C to 45°F (-13°C to 113°F)

<sup>1</sup> Typical colour temperature range: +/- 5 %  
<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %



\*This product complies with UL1598C Standard for LED luminaire Retrofit kits. Not suitable for hazardous location.

### ADDITIONAL INFORMATION

ONLY FOR BALLAST BYPASS INSTALLATION IN 277-347V APPLICATIONS. NOT FOR USE IN 120V DIRECT LINE VOLTAGE APPLICATIONS.  
 Direct replacement for 54 watts lamps only.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

