



Main

Range of product	Multi9
Product or Component Type	Connector
Accessory / separate part category	Connection accessory
Quantity per Set	Set of 4

Complementary

Line Rated Current	63 A
[Ui] Rated Insulation Voltage	1000 V
Connection pitch	0.71 in (18 mm)
Standards	UL 486E
Product certifications	CURus[RETURN]IEC
Color	White RAL 9001)
Connections - terminals	Screw terminal top connector 0.01...0.05 in ² (6...35 mm ²) rigid Screw terminal top connector 0.01...0.05 in ² (6...35 mm ²) flexible
Tightening torque	30.98 lbf.in (3.5 N.m)
Range compatibility	Multi9 Multi9 C60 C60BP comb busbar

Ordering and shipping details

Category	00949-M9 GEN 2 CB UL489
Discount Schedule	DE2
GTIN	3606481192936
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.10 in (2.800 cm)
Package 1 Width	3.70 in (9.400 cm)
Package 1 Length	5.31 in (13.500 cm)
Package 1 Weight	5.29 oz (150.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	25
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	9.20 lb(US) (4.174 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.