

Insulated multi-taps

Aluminum multi-tap encapsulated cable blocks – One-way configuration



CSR 2/0



CSB 250-5 S

These dual-rated blocks can be used with copper or aluminum cable.

- Versatile design supports a wide range of cable sizes and number of outlets available in one-way configurations
- Clear PVC insulation enables safe and time-saving installation with no taping required
- Meets or exceeds ANSI C119.4 specifications



Aluminum multi-tap encapsulated cable blocks – One-way configuration

Clear Cat. no.	No. of outlets	Wire range (AWG or kcmil)	Screw size	Dimensions (in.)		
				Length	Width	Height
Splices						
CSR 2/0	2	#14–2/0	3/8 Hex	2 3/4	7/8	1 3/8
CSR 250	2	#6–250		4 1/8	1 1/8	2 1/8
CSR 350	2	#6–350		4 3/4	1 3/8	2 1/2
CSR 500	2	2/0–500		6 1/2	1 5/8	2 7/8
Cable blocks						
CSB 4-2 S	2	#4–#14	Slotted	1 1/8	1 5/8	1 5/16
CSB 4-3 S	3			1 9/16		
CSB 4-4 SAH*	4			2 1/16		
CSB 4-5 S	5			2 9/16		
CSB 4-6 S	6			3 1/16		
CSB 4-7 S	7			3 9/16		
CSB 4-8 SAH*	8			4 1/16		
CSB 2/0-2 S	2	2/0–#14	3/16 Hex	1 7/8	1 3/4	1 3/8
CSB 2/0-3 S	3			2 3/8		
CSB 2/0-4 S	4			3 1/8		
CSB 2/0-5 S	5			3 7/8		
CSB 2/0-6 S	6			4 5/8		
CSB 2/0-7 S	7			5 3/8		
CSB 2/0-8 S	8			6 1/8		
CSB 250-2 S	2	250–#6	5/16 Hex	1 7/8	2 5/8	2 1/8
CSB 250-3 S	3			2 27/32		
CSB 250-4 S	4			3 13/16		
CSB 250-5 S	5			4 25/32		
CSB 250-6 S	6			5 3/4		
CSB 250-7 S	7			6 3/4		
CSB 250-8 S	8			7 45/64		
CSB 350-2 S	2	350–#10	5/16 Hex	2 1/4	3 1/8	2 1/2
CSB 350-3 S	3			3 1/4		
CSB 350-4 S	4			4 1/4		
CSB 350-5 S	5			5 1/4		
CSB 350-6 S	6			6 1/4		
CSB 350-7 S	7			7 1/4		
CSB 350-8 S	8			8 1/4		
CSB 500-2 S	2	500–#6	5/16 Hex	2 7/8	3 3/16	2 3/4
CSB 500-3 S	3			4 1/8		
CSB 500-4 S	4			5 3/8		
CSB 500-5 S	5			6 5/8		
CSB 500-6 S	6			7 7/8		
CSB 500-7 S	7			9 1/8		
CSB 500-8 S	8			10 3/8		

* Not UL[®] listed, includes hex screw.

Insulated multi-taps

Aluminum multi-tap encapsulated cable blocks – Two-way configuration



CSB 500-8

These dual-rated blocks can be used with copper or aluminum cable.

- Versatile design supports a wide range of cable sizes and number of outlets available in one-way configurations

- Clear PVC insulation enables safe and time-saving installation with no taping required
- Meets or exceeds ANSI C119.4 specifications

Aluminum multi-tap encapsulated cable blocks – Two-way configuration



Clear Cat. no.	No. of outlets	Wire range (AWG or kcmil)	Screw size	Dimensions (in.)		
				Length	Width	Height
CSB 4-2	2	#4-#14	Slotted	1 $\frac{1}{8}$	1 $\frac{5}{8}$	1 $\frac{5}{16}$
CSB 4-3	3			1 $\frac{9}{16}$		
CSB 4-4	4			2 $\frac{1}{16}$		
CSB 4-5	5			2 $\frac{9}{16}$		
CSB 4-6	6			3 $\frac{1}{16}$		
CSB 4-7	7			3 $\frac{9}{16}$		
CSB 4-8	8			4 $\frac{1}{16}$		
CSB 2/0-2	2	2/0-#14	$\frac{3}{16}$ Hex	1 $\frac{5}{8}$	1 $\frac{3}{4}$	1 $\frac{3}{8}$
CSB 2/0-3	3			2 $\frac{3}{8}$		
CSB 2/0-4	4			3 $\frac{1}{8}$		
CSB 2/0-5	5			3 $\frac{7}{8}$		
CSB 2/0-6	6			4 $\frac{5}{8}$		
CSB 2/0-7	7			5 $\frac{3}{8}$		
CSB 2/0-8	8			6 $\frac{1}{8}$		
CSB 250-2	2	250-#6	$\frac{5}{16}$ Hex	1 $\frac{7}{8}$	2 $\frac{5}{8}$	2 $\frac{1}{8}$
CSB 250-3	3			2 $\frac{27}{32}$		
CSB 250-4	4			3 $\frac{13}{16}$		
CSB 250-5	5			4 $\frac{25}{32}$		
CSB 250-6	6			5 $\frac{3}{4}$		
CSB 250-7	7			6 $\frac{3}{4}$		
CSB 250-8	8			7 $\frac{45}{64}$		
CSB 350-2	2	350-#10	$\frac{3}{8}$ Hex	2 $\frac{1}{4}$	3 $\frac{1}{8}$	2 $\frac{1}{2}$
CSB 350-3	3			3 $\frac{1}{4}$		
CSB 350-4	4			4 $\frac{1}{4}$		
CSB 350-5	5			5 $\frac{1}{4}$		
CSB 350-6	6			6 $\frac{1}{4}$		
CSB 350-7	7			7 $\frac{1}{4}$		
CSB 350-8	8			8 $\frac{1}{4}$		
CSB 500-2	2	500-#6	$\frac{3}{8}$ Hex	2 $\frac{7}{8}$	3 $\frac{3}{16}$	2 $\frac{3}{4}$
CSB 500-3	3			4 $\frac{1}{8}$		
CSB 500-4	4			5 $\frac{3}{8}$		
CSB 500-5	5			6 $\frac{5}{8}$		
CSB 500-6	6			7 $\frac{7}{8}$		
CSB 500-7	7			9 $\frac{1}{8}$		
CSB 500-8	8			10 $\frac{3}{8}$		
CSB 750-2	2	750-1/0	$\frac{3}{8}$ Hex	3	3 $\frac{3}{8}$	2 $\frac{1}{4}$
CSB 750-3	3			4 $\frac{7}{16}$		
CSB 750-4	4			5 $\frac{3}{16}$		
CSB 750-5	5			7 $\frac{1}{4}$		
CSB 750-6	6			8 $\frac{5}{8}$		
CSB 750-7	7			10		
CSB 750-8	8			11 $\frac{17}{16}$		
CSB 750-9	9			12 $\frac{13}{16}$		
CSB 750-10	10			14 $\frac{1}{4}$		