MELTRIC
A COMPANY OF MARECHAL ELECTRIC



DS20 RECEPTACLE

33-14143

SPECIFICATIONS

20 A
600 VAC
Type 3R
10 hp

Rated Current (A)	20 A
Rated Voltage (V)	600 VAC
Horsepower Rating	10 hp
Contact Configuration	3P+G
Auxiliary Contacts	NO AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 3R IP 55 IP
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	POLY
Metal Type	
Product Color	BLUE
Thread Size	
Cable Range	
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	14 AWG – 8 AWG SCREW TERMINAL
Hazardous Ratings	
Applicable Standards	UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13
Option(1)	
Option(2)	
Option(3)	
Option(4)	

Accessory Size	2
Base Drawing Number	33-14xxx.PDF
Catalog	meltric-catalog-ds20-en.pdf