



The GU24 socket and base system was designed to replace the Edison socket and base in energy efficient lighting fixtures to ensure that fixtures cannot be operated with an incandescent lamp. All STANDARD GU24 based lamps can be used in enclosed fixtures. Operating temperatures: non-dimmable: -23 °C/-10 °F to 55 °C/131 °F and dimmable: -18 °C/0 °F to 50 °C/123 °F.

Low profile spiral



Spiral (GU24)



Dimmable spiral (GU24)



Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)
<b>Low Profile Spiral</b>									
	MOL : 2 7/32 in. (58 mm) Dia. : 3 1/4 in. (79 mm)								
60289	CF13/30K/SPIRAL/LP/GU24/STD	13	GU24	3 000	82	10 000	900	48	60
<b>Spirals</b>									
	13 W: MOL : 3 5/16 in. (92 mm) Dia. : 1 13/16 in. (46 mm) 18 W: MOL : 4 1/32 in. (112 mm) Dia. : 1 1/8 in. (54 mm) 23 W: MOL : 4 13/32 in. (112 mm) Dia. : 1 1/8 in. (54 mm)								
61842	CF13/T2/27K/SPIRAL/GU24/STD	13	GU24	2 700	82	10 000	900	48	60
61843	CF13/T2/35K/SPIRAL/GU24/STD	13	GU24	3 500	82	10 000	880	48	60
61844	CF13/T2/41K/SPIRAL/GU24/STD	13	GU24	4 100	82	10 000	880	48	60
61845	CF18/T2/27K/SPIRAL/GU24/STD	18	GU24	2 700	82	10 000	1 150	48	75
61846	CF23/T2/27K/SPIRAL/GU24/STD	23	GU24	2 700	82	10 000	1 600	48	100
61847	CF23/T2/41K/SPIRAL/GU24/STD	23	GU24	4 100	82	10 000	1 600	48	100
<b>Spirals</b>									
	13 W: MOL : 3 15/16 in. (100 mm) Dia. : 1 13/16 in. (50 mm) 23 W: MOL : 4 7/32 in. (123 mm) Dia. : 2 1/8 in. (54 mm)								
60920*	CF13/D/27K/SPIRAL/GU24/STD	13	GU24	2 700	82	10 000	800	48	60
60921*	CF23/D/27K/SPIRAL/GU24/STD	23	GU24	2 700	82	10 000	1 500	48	100



# GU24 based lamps