

TM
TMX 30 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Similar to illustration

Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation. There are five different lengths (12, 15, 18, 20 and 30 mm) and eleven sizes - a marker type for all sleeves.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

General ordering data

| | |
|------------|---|
| Type | TMX 30 V0 |
| Order No. | 1866680000 |
| Version | TM, Socket x 20 mm, PVC, Colour: Transparent, Conductor O.D.: 10 - 317 mm |
| GTIN (EAN) | 4032248436958 |
| Qty. | 400 pc(s). |

Creation date November 2, 2020 3:36:45 PM CET

Catalogue status 23.10.2020 / We reserve the right to make technical changes.

TM
TMX 30 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|--------|-----------------|------------|
| Width | 20 mm | Width (inches) | 0.787 inch |
| Height | 30 mm | Height (inches) | 1.181 inch |
| Net weight | 0.62 g | | |

General data

| | | | |
|-----------------------------|-------------|---------------------------|---------------------------|
| Colour | Transparent | Material | PVC |
| Operating temperature range | -40...80 °C | Recommended industries | Transportation, Machinery |
| Type of printing | neutral | UL 94 flammability rating | V-0 |
| Width | 20 mm | | |

Conductor and cable markers

| | | | |
|-------------------------------|--------------------|-------------------------------|---------------------|
| Conductor O.D. | 10 - 317 mm | Conductor O.D., max. | 317 mm |
| Conductor O.D., min. | 10 mm | Conductor cross-section, max. | 150 mm ² |
| Conductor cross-section, min. | 16 mm ² | | |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| eClass 9.0 | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | UNSPSC | 44-12-17-08 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |

Data sheet

TM
TMX 30 V0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

