

PermaGround™ Ground Clamp Connectors Single Wire

- Manufactured from copper alloy
- Furnished with silicon bronze bolt, nut, and lock washer
- Mountable for surfaces up to 1/4" thick
- UL 467 Listed for grounding and bonding up to 250kcmil as well as UL 486 A/B
- Provides maximum conductivity
- For clamping conductors to flat surfaces
- Fits standard grounding bus bar and various flat plate metal surfaces
- Suitable for direct burial in earth or concrete




Fig. 1




Fig. 2




Fig. 3

Item ID	Figure Number	Conductor Range	A (in)	B (in)	C (in)	Bolt Size
GM-1	1	4str-8sol	1.250	1.000	1.625	3/8
GM-2	1	2/0str-4sol	1.625	1.125	1.750	3/8
GM-3	1	250kcmil-2/0sol	2.125	1.500	2.000	1/2
GM-4	1	500kcmil-300kcmil	2.375	1.625	2.500	1/2
GM-5	1	750kcmil-500kcmil	3	1.75	3	5/8
GM-6	1	1000kcmil-750kcmil	3.5	1.875	3.125	5/8
GMS-1	2	4str-8sol	1.25	1	1.625	3/8
GMS-2	2	2/0str-4sol	1.625	1.125	1.75	3/8
GMS-3	2	250kcmil-2/0sol	2.125	1.5	2	1/2
GMS-4	2	500kcmil-300kcmil	2.375	1.625	2.5	1/2
GMS-5	2	750kcmil-500kcmil	3	1.75	3	5/8
GMS-6	2	1000kcmil-750kcmil	3.5	1.875	3.125	5/8
GWL-1	3	4str-8sol	1.125	1.5	1.375	3/8
GWL-2	3	4str-8sol	1.75	1.75	1.875	1/2
GWL-3	3	2/0str-3str	1.688	2	1.875	3/8
GWL-4	3	2/0str-3str	1.813	2.125	1.875	1/2
GWL-5	3	250kcmil-3/0str	2.25	2.25	2.375	3/8
GWL-6	3	250kcmil-3/0str	2.25	2.375	2.375	1/2
GWL-7	3	250kcmil-3/0str	2.25	2.5	2.375	5/8