

# LC1DVK12M7

Capacitor contactor, Tesys Deca, 63kVAR at 400/415V 50Hz, 220V AC 50/60Hz coil, screw clamp terminals





## Main

Range	TeSys
Product name	TeSys LC1D.K TeSys Deca
Product or Component Type	Capacitor duty contactor
Device short name	LC1DWK
Device Application	Control
Contact application	Power factor correction
Utilisation category	AC-6b
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit 690 V AC 50/60 Hz
Reactive power rating	35 Kvar 230 V AC 50 Hz 140 °F (60 °C) 63 Kvar 400 V AC 50 Hz 140 °F (60 °C) 67 Kvar 440 V AC 50 Hz 140 °F (60 °C) 104 Kvar 690 V AC 50 Hz 140 °F (60 °C) 30 Kvar 230 V AC 60 Hz 140 °F (60 °C) 60 Kvar 460 V AC 60 Hz 140 °F (60 °C) 80 kvar 575 V AC 60 Hz 140 °F (60 °C)
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	220 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 2 NC instantaneous
Electrical durability	300000 Cycles 400 V 200000 cycles 690 V
Mounting Support	DIN rail Plate
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product Certifications	IECEE CB Scheme[RETURN]UL[RETURN]CSA[RETURN]UKCA
Connections - terminals	Control circuit: screw clamp terminals 1 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid Control circuit: screw clamp terminals 2 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid Control circuit: screw clamp terminals 1 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.00... 0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible with cable end Power circuit: connector 1 0.01...0.08 in <sup>2</sup> (4... 50 mm <sup>2</sup> ) - cable stiffness: solid Power circuit: connector 2 0.01...0.04 in <sup>2</sup> (4... 25 mm <sup>2</sup> ) - cable stiffness: solid Power circuit: connector 1 0.01...0.08 in <sup>2</sup> (4... 50 mm <sup>2</sup> ) - cable stiffness: flexible without cable end Power circuit: connector 2 0.01...0.04 in <sup>2</sup> (4... 25 mm <sup>2</sup> ) - cable stiffness: flexible without cable end Power circuit: connector 1 0.01...0.08 in <sup>2</sup> (4... 50 mm <sup>2</sup> ) - cable stiffness: flexible with cable end Power circuit: connector 2 0.01...0.02 in <sup>2</sup> (4... 16 mm <sup>2</sup> ) - cable stiffness: flexible with cable end
Tightening torque	Power circuit 79.66 lbf.in (9 N.m) connector Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals
Maximum operating rate	240 cyc/h

## Complementary

Auxiliary contacts type	Mechanically linked 1 NO + 2 NC IEC 60947-5-1
-------------------------	---

## Environment

IP degree of protection	IP20 front face IEC 60529
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Operating altitude	0...9842.52 ft (0...3000 m)
Height	7.09 in (180 mm)
Width	3.35 in (85 mm)
Depth	6.06 in (154 mm)
Net Weight	3.64 lb(US) (1.65 kg)

## Ordering and shipping details

Category	22359-CTR,TESYS D,OPEN,80-150A AC&DC
Discount Schedule	I12
GTIN	3389110060539
Returnability	No
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.12 in (13.000 cm)
Package 1 Width	6.69 in (17.000 cm)
Package 1 Length	7.48 in (19.000 cm)
Package 1 Weight	3.94 lb(US) (1.786 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	48.68 lb(US) (22.082 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	48
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	31.50 in (80.000 cm)
Package 3 Length	23.62 in (60.000 cm)
Package 3 Weight	212.37 lb(US) (96.328 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Contractual warranty

Warranty	18 months
----------	-----------