

# 8501XO40XLV02

NEMA Control Relay, Type X, latching, 10A resistive at 600 VAC, 4 normally open contacts, 110/120 VAC 50/60 Hz coil



## Main

Range	8501X
Relay Type	Latching
Product	Relay
Current Rating	10 A AC 5 A DC
Contact Configuration	4 NO 4 standard contact cartridges
Number of Poles	4P
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Voltage Rating	600 V AC
Mounting Type	Panel
Operating Temperature	-40...160 °F (-40...71 °C)
Electrical Connection	Screw clamp terminals
Certifications	CE[RETURN]CSA[RETURN]UL Listed
Operating Time	15 ms - pick-up 13 ms - drop-out
Height	3.50 In (88.90 mm) 3.50 in (88.90 mm)
Width	2.23 In (56.64 mm) 2.23 in (56.64 mm)
Depth	6.54 In (166.12 mm) 6.54 in (166.12 mm)

## Ordering and shipping details

Category	21158-8501 XO (AC)
Discount Schedule	CP2
GTIN	785901028505
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.30 in (8.382 cm)
Package 1 Width	4.30 in (10.922 cm)
Package 1 Length	9.30 in (23.622 cm)
Package 1 Weight	2.95 lb(US) (1.338 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
RECh Regulation	<a href="#">RECh Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes

---

China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---