



Main

Product	Double Throw Safety Switch
Current Rating	30 A
Certifications	CSA
Enclosure Rating	NEMA 1 galvanized steel
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number of Poles	2
Voltage Rating	240 V AC
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper

Complementary

Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in ² (13.3 mm ²) (AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) (AWG 14...AWG 10)
Width	9.75 in (247.65 mm)
Height	10 in (254.00 mm)
Depth	4.75 in (120.65 mm)



Ordering and shipping details

Category	00153-C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	785901995685
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.88 in (12.4 cm)
Package 1 Width	10.00 in (25.4 cm)
Package 1 Length	10.98 in (27.9 cm)
Package 1 Weight	7.30 lb(US) (3.31 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations