



GREENLEE.
A Textron Company

MADE FOR THE TRADE!™

PUNCH 3/4" COND SPEED (POP)(7212SP-3/4P)

"Punch, 3/4"" conduit size, SPEED PUNCH™ System



Image
Unavailable

Cat No: 52063423

UPC No: 783310009528

Description

- SPEED PUNCH® saves time and money with every hole.
- Up to 3X's faster setup and disassembly.
- No-Thread punch design eliminates cross-threading.
- Available in 3/4" - 2" conduit sizes and punch kits.

Specifications

- Application : For punching conduit sized holes in mild steel, aluminum, fiberglass, and plastic.
- Capacity : Mild steel up through 10 gauge (3.5 mm).
- Diameter : Actual hole size: 1.115" (28.3 MM)
- Draw Studs : Std. Draw Stud: 7212SP11 (3/4" x 4.77"). Long Draw Stud: 7212SP12 (3/4" x 5.63")
- For use w/746 Hydraulic Ram.
- Driver : Use with Greenlee Hydraulic Drivers - Quick Draw® Flex (7704SB), Quick Draw® Standard (7804SB), QUICK DRAW 90® (7904SB) AND HYDRAULIC RAM (746 W/7212SP12 LONG DRAW STUD), OR LS50 BATTERY-POWERED DRIVER (LS50L11A).
- Material : Carbon Steel, Nickel Plated
- Minimum Pilot Hole : Recommended size: 7/8" (22.2 MM)
- Operation : Must be used with other SPEED PUNCH® System components
- Sub Brand : SPEED PUNCH®#174
- Type : Knockout Punches
- Weight : 0.10 lbs. (0.04 kg)