

Product data sheet

Characteristics

8903SYG2V02S

Contact, Type S, multipole lighting,
electrically held, 400A, 3 pole, 110/120 VAC
50/60 Hz coil, NEMA 1



Main

Type	S
------	---

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	400 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	65.75 in (1670 mm)
Depth	13.11 in (333 mm)
Width	20.20 in (513 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL Listed[RETURN]CSA

Ordering and shipping details

Category	30156-8903 S:ELEC HELD LTG CONTR
Discount Schedule	SQ2L
GTIN	785901024101
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	65.75 in (167.0 cm)
Package 1 Width	20.20 in (51.3 cm)
Package 1 Length	13.11 in (33.3 cm)
Package 1 Weight	64.00 lb(US) (29.03 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------