

Main

Range	Square D
Product or Component Type	Power supply
Device Application	Power supply

Complementary

Kw Rating	7.5 W
Supply voltage limits	85...264 V AC 105...370 V DC
Supply circuit type	AC/DC
Network frequency	50/60 Hz +/- 5 %
Primary voltage	100...240 V 0.17 A AC 50/60 Hz 110...340 V DC
Secondary voltage	24 V DC
Associated fuse rating	2 A
Inrush current	50 A
Maximum leakage current	0.75 mA
Maximum output current	300 mA
Protection Type	Against short-circuits
Net Weight	5.29 oz (150 g)

Environment

Relative humidity	20...90 % without condensation
Ambient Air Temperature for Operation	14...140 °F (-10...60 °C)
Ambient Air Temperature for Storage	-22...185 °F (-30...85 °C)

Ordering and shipping details

Category	09794-POWERLOGIC BCPM ACCESSORIES
Discount Schedule	PL1
GTIN	3606486796306
Returnability	No
Country of origin	TW

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.89 in (4.8 cm)
Package 1 Width	2.87 in (7.3 cm)
Package 1 Length	3.27 in (8.3 cm)
Package 1 Weight	6.41 oz (181.82 g)

Offer Sustainability

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

EU RoHS Directive

Compliant [EU RoHS Declaration](#)

Contractual warranty

Warranty

18 months