



Communication Hardware

CLAMPS & POLE STEPS

Parallel Groove Clamp

Top and bottom castings are malleable iron, Hot dip galvanized.
Spacer is tinned bronze for use on aluminum and copper.

Cat.No.	Cable Sizes		Std.Pkg.	Wt.-lbs./ C
	Maximum	Minimum		
4468PGC-38	4/0-4/0 Str	# 6 SOL - # 8 SOL	100	56



4468PGC-38

Standard Pole Step

Threads are fetter drive-driving surface is flat.

Cat.No.	D	L	Std. Pkg.	Wt.-lbs./ C
10SPS	5/8"	10"	50	90



10SPS

Wire Clip

Made of 16 gage galvanized steel.

Cat.No.	Hole Size	Wire Size	Std. Pkg.	Wt.-lbs./ C
1CDW	3/16	5/16	500	1



1CDW

Clamp

Lashing Wire Clamp - Galvanized formed steel clamp used to terminate the cable lashing wire.

Cat.No.	Strand Size	Std. Pkg.	Wt.-lbs./ C
LWC10	1/4 - 7/16	100	3




LWC10

Dead End Clamp

For Copper wire and ACSR.

Cat.No.	Description	No. of Clamps	Std. Pkg.	Wt.-lbs./ C
610DC	6 SOL Copper - 1/0 str. copper	1	100	55



610DC

1 3/4

1 1/4