



## Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Product or Component Type | Electrically Held Lighting Contactor |
| Range of Product          | 8903L                                |
| Control Circuit           | Separate control circuit             |

## Complementary

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Control Circuit Voltage         | 220 V AC 50 Hz<br>240 V AC 60 Hz  |
| Inrush power in VA              | 25 VA 60 Hz<br>140 VA 50 Hz       |
| Hold-in power consumption in VA | 30 VA 60 Hz<br>30 VA 50 Hz        |
| Current Rating                  | 20 A tungsten<br>30 A fluorescent |
| Number of Poles                 | 3P 3 NO                           |
| Control Unit                    | No control units                  |
| Pilot Light                     | No indicator                      |
| Electrical Connection           | Screw-clamp terminals             |
| Height                          | 5.00 in (127 mm)                  |
| Depth                           | 3.11 in (79 mm)                   |
| Width                           | 2.87 in (73 mm)                   |

## Environment

|                        |                         |
|------------------------|-------------------------|
| Enclosure Type         | Not rated (open device) |
| Product Certifications | UL Listed[RETURN]CSA    |

## Ordering and shipping details

|                   |                       |
|-------------------|-----------------------|
| Category          | 21321-8903 L (NOT LX) |
| Discount Schedule | CP1                   |
| GTIN              | 785901341192          |
| Returnability     | No                    |
| Country of origin | MX                    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 4.50 in (11.43 cm)    |
| Package 1 Width              | 6.00 in (15.24 cm)    |
| Package 1 Length             | 7.00 in (17.78 cm)    |
| Package 1 Weight             | 2.54 lb(US) (1.15 kg) |

## Offer Sustainability

|                             |   |
|-----------------------------|---|
| Sustainable offer status    | Green Premium product                         |
| REACH Regulation            | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC          | Yes   |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free      | Yes   |
| Mercury free                | Yes   |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information  | <a href="#">Yes</a>                           |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a> |
| Circularity Profile         | No need of specific recycling operations      |
| PVC free                    | Yes   |
| Halogen content performance | Halogen free plastic parts product            |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|