CSA Metallic Liquid Tight Conduit - REELS

Metallic - BLACK



Features

- Rated for -40°C to 75°C Dry, 75°C Oil
- Smooth metal interior for easy wire pulling
- Flame test rating of FT-4 per CSA, C22.2 No.56
- Standard colour is black.
- Resists sunlight, oil, heat and chemical degradation.
- Suitable for direct burial and wet location applications.
- Accepts standard metallic liquid tight fittings

Applications

- Indoor or outdoor use

Standard Material

- Galvanized Steel Core with FT4 PVC Jacket

Certification

- CSA File #: 608419 (3/8"-2"), 244054 (2½"-4")

Catalog Number	Size	Metric Designator	UPC Code	Meters/ Coil	Skid Qty	Inside Dia Min.In.	Outside Di Max.In.	Bend Radius In.	Weight kg/m (lbs/ft)
38LT150	3/8"	12	11998	150	600	0.484	0.710	4.000	.35(.235)
38LT300	3/8"	12	11999	300	600	0.484	0.710	4.000	.35(.235)
05LT150	1/2"	16	11140	150	600	0.622	0.840	6.500	.42(.282)
05LT300	1/2"	16	11142	300	600	0.622	0.840	6.500	.42(.282)
07LT150	3/4"	21	11154	150	300	0.820	1.050	8.500	.55(.369)
07LT300	3/4"	21	11156	300	600	0.820	1.050	8.500	.55(.369)
10LT150	1"	27	11234	150	300	1.041	1.315	13.000	.80(.537)
12LT75	1¼"	35	11333	75	150	1.380	1.660	16.000	1.12(.758)
15LT75	1½"	41	11464	75	150	1.575	1.900	18.000	1.45(.973)
20LT30	2"	53	11595	30	60	2.020	2.375	22.250	1.67(1.121)
20LT60	2"	53	11596	60	120	2.020	2.375	22.250	1.67(1.121)
25LT30	2½"	63	11748	30	30	2.480	2.875	29.250	2.70(1.812)
30LT30	3"	78	11885	30	30	3.070	3.50	35.00	3.79(2.543)
40LT30	4"	91	13345	30	30	4.000	4.50	48.00	5.39(3.617)

NOTE: Cut lengths are available on 2½" to 4" diameter liquid tight conduit.

Please consult our Inside Sales desk or your local Nesco Sales Representative with your requirements.

Nesco Inc.
1039 Cardiff Blvd., Mississauga, ON L5S 1P4
TF: (866) 466-3726 Tel: (905) 793-2218 Fax: (905) 793-2268
www.nescocanada.com