



Main

Product	Adaptor
Range	I-Line

Complementary

Rated Current	1600 A aluminium
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	12 in (304.80 mm)
Material	Aluminium: busbar
I-LINE Value End	Slot
Number of Phases	3 phase
For Use with	Busbar trunking 1600 A aluminium
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire
Mounting Location	Indoor

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

Ordering and shipping details

Category	20010-1600A AL FEEDER BUS IP54 THERMAL
Discount Schedule	PE8
GTIN	785901016823
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.88 in (14.935 cm)
Package 1 Width	8.84 in (22.454 cm)
Package 1 Length	13.00 in (33.02 cm)
Package 1 Weight	30.00 lb(US) (13.608 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------