

# LC1G330KUEN

Contactor, high power, TeSys Giga, standard version, 3 pole/NO, AC-3  $\leq 440\text{V}$  330A, 100-250VAC/DC coil



## Main

Range	TeSys
Range of Product	TeSys Giga
Product or Component Type	Contacteur
Device short name	LC1G
Contactor application	Power switching Motor control
Utilisation category	AC-1 AC-3 AC-3e AC-4 AC-5a AC-5b AC-6a AC-6b AC-8a AC-8b DC-1 DC-3 DC-5
Poles description	3P
[Ue] rated operational voltage	$\leq 1000\text{ V AC } 50/60\text{ Hz}$ $\leq 460\text{ V DC}$
[Ie] rated operational current	440 A (at $<104\text{ }^\circ\text{F}$ ( $40\text{ }^\circ\text{C}$ )) at $\leq 1000\text{ V AC-1}$ 330 A (at $<140\text{ }^\circ\text{F}$ ( $60\text{ }^\circ\text{C}$ )) at $\leq 440\text{ V AC-3}$
[Uc] control circuit voltage	100...250 V AC 50/60 Hz 100...250 V DC
Control circuit voltage limits	Operational: 0.8 Uc Min...1.1 Uc Max (at $<140\text{ }^\circ\text{F}$ ( $60\text{ }^\circ\text{C}$ )) Drop-out: 0.1 Uc Max...0.45 Uc Min (at $<140\text{ }^\circ\text{F}$ ( $60\text{ }^\circ\text{C}$ ))

## Complementary

[Uimp] rated impulse withstand voltage	8 kV
Overtoltage category	III
[Ith] conventional free air thermal current	440 A (at $104\text{ }^\circ\text{F}$ ( $40\text{ }^\circ\text{C}$ ))
Rated breaking capacity	2940 A at 440 V
[Icw] rated short-time withstand current	2.65 KA - 10 s 1.8 KA - 30 s 1.3 KA - 1 min 0.9 KA - 3 min 0.75 KA - 10 min
Associated fuse rating	400 A aM at $\leq 440\text{ V}$ for motor 250 A aM at $\leq 690\text{ V}$ for motor 500 A gG at $\leq 690\text{ V}$
Average impedance	0.000144 Ohm
[Ui] rated insulation voltage	1000 V
Power dissipation per pole	30 W AC-1 - Ith 440 A 16 W AC-3 - Ith 330 A
Compatibility code	LC1G
Pole contact composition	3 NO
Auxiliary contact composition	1 NO + 1 NC

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Motor power kW	<p>90 KW at 230 V AC 50/60 Hz (AC-3e)  160 KW at 400 V AC 50/60 Hz (AC-3e)  160 KW at 415 V AC 50/60 Hz (AC-3e)  185 KW at 440 V AC 50/60 Hz (AC-3e)  200 KW at 500 V AC 50/60 Hz (AC-3e)  220 KW at 690 V AC 50/60 Hz (AC-3e)  185 KW at 1000 V AC 50/60 Hz (AC-3e)  90 KW at 230 V AC 50/60 Hz (AC-3)  160 KW at 400 V AC 50/60 Hz (AC-3)  160 KW at 415 V AC 50/60 Hz (AC-3)  200 KW at 440 V AC 50/60 Hz (AC-3)  200 KW at 500 V AC 50/60 Hz (AC-3)  220 KW at 690 V AC 50/60 Hz (AC-3)  185 KW at 1000 V AC 50/60 Hz (AC-3)  90 KW at 230 V AC 50/60 Hz (AC-4)  160 KW at 400 V AC 50/60 Hz (AC-4)  160 KW at 415 V AC 50/60 Hz (AC-4)  185 KW at 440 V AC 50/60 Hz (AC-4)  200 KW at 500 V AC 50/60 Hz (AC-4)  220 KW at 690 V AC 50/60 Hz (AC-4)  185 kW at 1000 V AC 50/60 Hz (AC-4)</p>
Maximum Horse Power Rating	<p>100 Hp at 200/208 V 60 Hz  125 Hp at 230/240 V 60 Hz  250 Hp at 460/480 V 60 Hz  300 hp at 575/600 V 60 Hz</p>
Irms rated making capacity	3830 A at 440 V
Coil technology	Built-in bidirectional peak limiting
Mechanical durability	8 Mcycles
Inrush power in VA (50/60 Hz, AC)	700 VA
Inrush power in W (DC)	645 W
Hold-in power consumption in VA (50/60 Hz, AC)	15.0 VA
Hold-in power consumption in W (DC)	9.1 W
Operating time	<p>40...70 ms closing  15...50 ms opening</p>
Maximum operating rate	<p>600 Cyc/H AC-3  600 Cyc/H AC-3e  300 Cyc/H AC-1  150 cyc/h AC-4</p>
Connections - terminals	<p>Power circuit: bar 2 - busbar cross section: 32 x 10 mm  Power circuit: lugs-ring terminals 1 0.29 in<sup>2</sup> (185 mm<sup>2</sup>)  Power circuit: bolted connection  Control circuit: push-in 1 0.00...0.00 in<sup>2</sup> (0.2...2.5 mm<sup>2</sup>) - cable stiffness: solid stranded without cable end  Control circuit: push-in 1 0.00...0.00 in<sup>2</sup> (0.25...2.5 mm<sup>2</sup>) - cable stiffness: flexible with cable end  Control circuit: push-in 2 0.00...0.00 in<sup>2</sup> (0.5...1.0 mm<sup>2</sup>) with cable end  Control circuit: push-in 0.00...0.00 in<sup>2</sup> (0.75...2.5 mm<sup>2</sup>) - cable stiffness: solid stranded without cable end  Control circuit: push-in 0.00...0.00 in<sup>2</sup> (0.75...2.5 mm<sup>2</sup>) - cable stiffness: flexible with cable end</p>
Connection pitch	1.77 in (45 mm)
Mounting Support	Plate
Standards	<p>EN/IEC 60947-4-1  EN/IEC 60947-5-1  UL 60947-4-1  CSA C22.2 No 60947-4-1  JIS C8201-4-1  JIS C8201-5-1</p>
Product Certifications	<p>CB  Scheme[RETURN]CCC[RETURN]cULus[RETURN]EAC[RETURN]CE[RETURN]UKCA[RETURN]  RO-MR by DNV-GL</p>
Tightening torque	309.78 lbf.in (35 N.m)
Height	8.86 in (225 mm)
Width	5.51 in (140 mm)
Depth	8.90 in (226 mm)
Net Weight	16.53 lb(US) (7.5 kg)

## Environment

IP degree of protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Ambient Air Temperature for Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Mechanical robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Color	Dark grey
Protective treatment	TH
Permissible ambient air temperature around the device	-40...158 °F (-40...70 °C) at Uc

## Ordering and shipping details

Category	22329-TESYS GIGA CONTACTORS
Discount Schedule	I12
GTIN	3606481921970
Returnability	Yes

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.20 in (31.0 cm)
Package 1 Width	8.86 in (22.5 cm)
Package 1 Length	12.20 in (31.0 cm)
Package 1 Weight	16.48 lb(US) (7.473 kg)
Unit Type of Package 2	S06
Number of Units in Package 2	4
Package 2 Height	41.34 in (105 cm)
Package 2 Width	23.62 in (60 cm)
Package 2 Length	31.50 in (80 cm)
Package 2 Weight	89.29 lb(US) (40.5 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product