



Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part type	Jumper cable
Accessory / separate part category	Connection accessory
Accessory / separate part destination	safety light curtain master/slave XCSR RFID safety switch

Complementary

Product compatibility	XUSL2 XUSL4 XCSRC.2M12
Connector type	M12 female 5 pins straight
Wire insulation material	PUR
Collar material	Nickel plated brass
Cable outer diameter	0.20 in (5 mm)
Cable composition	5 x 0.34 mm ²
Cable length	16.40 ft (5 m)

Environment

IP degree of protection	IP67 IP65 IP69K
-------------------------	-----------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	6.84 oz (194 g)
Package 1 Height	1.42 in (3.6 cm)
Package 1 width	6.65 in (16.9 cm)
Package 1 Length	7.05 in (17.9 cm)
Unit Type of Package 2	BAG
Number of Units in Package 2	1

Package 2 Weight	7.20 oz (204 g)
Package 2 Height	1.57 in (4 cm)
Package 2 width	6.69 in (17 cm)
Package 2 Length	7.48 in (19 cm)
Unit Type of Package 3	S02
Number of Units in Package 3	20
Package 3 Weight	10.00 lb(US) (4.535 kg)
Package 3 Height	5.91 in (15 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes