



Main

Range of Product	Altivar
Product or Component Type	Communication module
Accessory / separate part category	Communication accessories

Complementary

Product Compatibility	Lexium 32M
Range compatibility	Altivar 32 Altivar Machine ATV340 except Sercos drives Altivar Easy 610 Lexium 32 Altivar&Nbsp;Process ATV900 Altivar&Nbsp;Process ATV600 Altivar Machine ATV320 Altivar Process Modular
Communication port protocol	Profibus DP V1
Electrical connection	1 female connector SUB-D 9
Transmission Rate	9.6 kbps...12 Mbps
Addressing	1...126 configurable by graphic terminal/SoMove software Configuration settings
Communication service	4 configurable telegrams Mapping of the process data from the master Parameters management compliant with PROFIdrive V4.1 Several DP V1 messaging modes Drive profile native ATV32 IEC 61800-7-201 (CiA 402)
Display type	1 LED RUN 1 LED bus fault (BF)
Diagnostic function	Diagnostic data with VSD status Host drive handled from two masters (MS0 and MS1) Standard identification and maintenance requests
Bus profile	PROFIdrive CiA 402

Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

Ordering and shipping details

Category	18263-LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	3606480177583
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.85 in (4.700 cm)
Package 1 Width	2.40 in (6.100 cm)
Package 1 Length	3.54 in (9.000 cm)
Package 1 Weight	2.15 oz (61.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	14.65 lb(US) (6.643 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------