

Technical Information Bulletin

LED Linear Tubes



Date: _____ Name of distributor: _____
 In hands date of project: _____ Client #: _____
 Project name/Number: _____ Name of end user: _____

ORDERING INFORMATION

Order code: 67378
 Description: T8/15W/840/48/BYP/277-347/ND/STD
 UPC: 69549673786
 Case quantity: 25



MOL: 48 in. (1 200 mm) Dia. : 1 in. (26 mm)

PHYSICAL DATA

Shape: T8
 Base: G13
 Material: Glass

PERFORMANCE DATA

Install method: Ballast bypass
 Lamp Watts (W): 15
 Volts (VAC): 277-347
 Colour temperature (K)¹: 4 000
 Initial Lumens (lm)²: 2 200
 Initial lumens per watt (lm/W): 147
 Life L70 (hrs): 50 000
 CRI: 82
 Operating temperature range: -25°C to 45°F (-13°C to 113°F)

¹ Typical colour temperature range: +/- 5 %
² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %



*This product complies with UL1598C Standard for LED luminaire Retrofit kits. Not suitable for hazardous location.

ADDITIONAL INFORMATION

ONLY FOR BALLAST BYPASS INSTALLATION IN 277-347V APPLICATIONS. NOT FOR USE IN 120V DIRECT LINE VOLTAGE APPLICATIONS.
 Direct replacement for 25, 28, 30 & 32 watts T8 lamps only.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____

Date: _____

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.
 Data is based upon tests performed in a controlled environment and representative of relative performance.
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.