

Product data sheet

Characteristics

CHOM3060M200GC

Loadcentre, Homeline, 1 phase, 30 spaces, 60 circuits, 200A main breakers, Type 3R, gnd bar, combo cover



Main

Range of Product	Homeline
Product or Component Type	Load Center
Line Rated Current	200 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Wall mount
Short-circuit current	22 kA

Complementary

Electrical Connection	Lugs
AWG gauge	AWG 4...250 kcmil aluminium/copper
Load center type	Main breaker
Number of spaces	30
Number of circuits	60
Number of tandem circuit breakers	30
Phase	1 phase
Cover type	Combination flush/surface cover
Device Composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Cover colour	White
Box number	10

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 1 indoor)
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)

Ordering and shipping details

Category	00199-DE5 MISC. SERVICE PARTS
Discount Schedule	DE5
GTIN	785901677352
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.50 in (13.97 cm)
Package 1 Width	32.30 in (82.042 cm)
Package 1 Length	16.00 in (40.64 cm)
Package 1 Weight	34.60 lb(US) (15.694 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations