



## Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	1P
Circuit Breaker Type	Standard
Ratings	HACR and Switching Duty rated
Electrical Connection	Pressure plate

## Complementary

Interrupt Rating	65 KA 120/240 V AC 50/60 Hz 65 kA 120 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening Torque	40.71 lbf.in (4.6 N.m)
Height	2.99 in (76 mm)
Width	0.75 in (19 mm)
Depth	2.91 in (74 mm)
Net Weight	0.33 lb(US) (0.150 kg)

## Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

## Ordering and shipping details

Category	00015-QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	785901255383
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.70 in (1.778 cm)
Package 1 Width	3.40 in (8.636 cm)
Package 1 Length	3.30 in (8.382 cm)
Package 1 Weight	4.38 oz (124.28 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.00 in (10.16 cm)
Package 2 Width	4.20 in (10.668 cm)
Package 2 Length	8.10 in (20.574 cm)

Package 2 Weight	2.85 lb(US) (1.294 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	8.60 in (21.844 cm)
Package 3 Width	8.20 in (20.828 cm)
Package 3 Length	17.10 in (43.434 cm)
Package 3 Weight	29.08 lb(US) (13.189 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

### Contractual warranty

Warranty	18 months
----------	-----------