

# Product data sheet

## Characteristics

# 8903SVO2V03

Contactor, Type S, multipole lighting,  
electrically held, 200A, 3 pole, 220/240 VAC  
50/60 Hz coil, open style



### Main

Product	Electrically Held Lighting Contactor
Type	S

### Complementary

Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Current Rating	200 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	9.13 in (232 mm)
Depth	6.50 in (165 mm)
Maximum Width	5.98 in (152 mm)

### Environment

Enclosure Type	Not rated (open device) surface none
Product certifications	UL Listed CSA

### Ordering and shipping details

Category	21325 - 8903 S (NOT S°C) ELECT.
Discount Schedule	CP1
GTIN	00785901153863
Nbr. of units in pkg.	1
Package weight(Lbs)	16.7 lb(US) (7.57 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

---

Warranty

18 months

---