

Product data sheet

Specifications



Mini circuit breaker, E-Frame, 20A, 1 pole, 277VAC, 65kA max, bolt on, 30mA ground fault protection [TAA]

EGB14020EPD

Product availability: Stock - Normally stocked in distribution facility

Main

Range	125 A Frame EDB-EGB-EJB
Product Type	Miniature circuit-breaker
Device Short Name	EGB
Earth-leakage Protection Class	Class B
Module Type	E-Frame
Trip Unit Rating	875 A

Complementary

Rated Current	20 A
Maximum Operating Voltage	277 V AC
AWG Gauge	AWG 14...AWG 6 copper AWG 12...AWG 4 aluminium
Breaking Capacity	35 kA 277 V AC 35 kA 240 V AC 65 kA 120 V AC 35 kA 120/240 V AC
Circuit Breaker Application	Switching Duty rated HACR rated HID rated
Earth-leakage Sensitivity	30 mA
Electrical Connection	Lugs aluminium
Holding Current	270 A
Local Signalling	Trip indicator
Mounting Mode	Bolt-on
Number of Poles	1
Number of Spaces	2
Number of Spaces Required	2
Product Destination	NF panelboard
Protect Type	Short-circuit Overload
Trip Unit Technology	Thermal-magnetic
Breaking Capacity Code	G
Tightening Torque	30.09 lbf.in (3.4 N.m) 0.004...0.02 in² (2.5...16 mm²) (AWG 14...AWG 6)
Height	6.64 in (168.66 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	1.96 in (49.78 mm)
Depth	4.05 in (102.87 mm)
Product Weight	2 lb(US) (0.9 kg)

Environment

Product Certifications	cULus
Ambient Air Temperature for Operation	104 °F (40 °C)

Ordering and shipping details

Category	US10DE200946
Discount Schedule	0DE2
GTIN	785901470458
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.500 in (6.350 cm)
Package 1 Width	5.500 in (13.970 cm)
Package 1 Length	7.300 in (18.542 cm)
Package weight(Lbs)	32.844 oz (931.134 g)

Compliance

Compliance	TAA Compliant
------------	---------------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	56 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	51 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	8781af64-acd9-485c-9a86-abcdfbd458e3
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again




Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No

Technical Illustration

Dimensions



All dimensions are approximate.
Also see technical drawings and/or documentation.