

Product Datasheet

Characteristic

XZCP1164L10

pre-wired connectors XZ - straight
female - M12 - 5 pins - cable PUR 10m



Main

accessory / separate part category	cabling accessory
accessory / separate part type	pre-wired connectors
series name	general purpose

Complementary

electrical connection	straight female connector, connector type: M12 5 pins (included earth pin)
cable connector fixing	screw-on
collar material	metal
status LED	without
cable length	10 m
cable outer diameter	0.23 in (5.9 mm)
cable composition	5 x 0.34 mm ²
wire insulation material	PUR
System Voltage	60 V AC 75 V DC
Line Rated Current	4 A
contact resistance	<= 5000 µOhm
insulating resistance	>= 1 GΩ
product weight	1.15 lb(US) (0.52 kg)

Environment

IP degree of protection	IP65 IP67 IP69K
ambient air temperature for operation	-40...176 °F (-40...80 °C) (static) 23...176 °F (-5...80 °C) (flexing)
ambient air temperature for storage	-40...176 °F (-40...80 °C)

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 0649 -
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------