



## Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	H-frame
Trip unit technology	Thermal-magnetic

## Complementary

Protection type	Circuit breaker
Mounting mode	Plug-in
[Ue] rated operational voltage	600 V AC
[In] rated current	45 A
Number of Phases	3 phases
Poles description	3P
Interrupt Rating	25 kA 240 V AC 18 kA 480 V AC 14 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	4-wire (integral ground bus)
AWG gauge	AWG 8...AWG 3/0 1 phase and neutral AWG 6...AWG 2/0 1 ground
Depth	9.13 in (232 mm)
Height	8.50 in (216 mm)
Width	21.69 in (551 mm)

## Environment

Product certifications	UL listed file E22182 CSA C22.2 No 27
------------------------	--

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Standards	UL 857
-----------	--------

---

### Packing Units

---

Package 1 Weight	32.00 lb(US) (14.515 kg)
------------------	--------------------------

---

### Offer Sustainability

---

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

---