



Main

Range of Product	PowerLogic T300
Device short name	HU250-EB
Product or Component Type	Empty modem box

Environment

IK degree of protection	IK07 IEC 62262
Relative humidity	95 % IEC 60068-2-30
Ambient Air Temperature for Operation	-40...185 °F (-40...85 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Fire resistance	1562 °F (850 °C)
Operating altitude	6561.68 ft (2000 m)
Product Certifications	CE
Height	1.18 in (30 mm)
Width	4.53 in (115 mm)
Depth	5.24 in (133 mm)
Net Weight	0.23 lb(US) (0.105 kg)

Ordering and shipping details

Category	08642-SAGE FEEDER RTU
Discount Schedule	RTU1
GTIN	3606480802874
Returnability	No
Country of origin	EG

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.14 in (2.9 cm)
Package 1 Width	4.49 in (11.4 cm)
Package 1 Length	5.24 in (13.3 cm)
Package 1 Weight	2.47 oz (70.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	4.25 lb(US) (1.929 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.