



Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	J-frame
Trip unit technology	Electronic, standard, Micrologic 3.2 S, LSI

Complementary

Protection type	Circuit breaker
Mounting mode	Plug-in
[Ue] rated operational voltage	600 V AC
[In] rated current	250 A
Number of Phases	3 phases
Poles description	3P
Interrupt Rating	65 kA 240 V AC 35 kA 480 V AC 18 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	3-wire (integral ground bus)
AWG gauge	AWG 6...AWG 2/0 1 ground AWG 3/0...350 kcmil 1 phase and neutral
Depth	9.13 in (232 mm)
Height	8.50 in (216 mm)
Width	21.69 in (551 mm)

Environment

Product certifications	UL listed file E22182 CSA C22.2 No 27
Standards	UL 857

IP degree of protection

IP54

Packing Units

Package 1 Weight

32.00 lb(US) (14.515 kg)

Offer Sustainability

Sustainable offer status

Green Premium product

REACH Regulation

[REACH Declaration](#)

EU RoHS Directive

Compliant
[EU RoHS Declaration](#)

Mercury free

Yes

RoHS exemption information

[Yes](#)

China RoHS Regulation

[China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)