

Product data sheet

Characteristics

NQSE184300F

Panelboard service entrance, NQ, main breaker, 300A, 84 pole spaces, 1 phase, 2 wire, flush mount, 22 in



Main

Device short name	NQ
Product or Component Type	Load Center
Cover type	Flush cover

Complementary

Line Rated Current	300 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Flush-mounted
Device mounting	Flush
Poles description	2-pole
AWG gauge	AWG 1/0 aluminium/copper
Load center type	Main breaker
Number of spaces	84
Phase	1 phase
Wiring configuration	2-wire
Enclosure Material	Galvanized Steel
Height	64 in (1625.60 mm)
Width	22 in (558.80 mm)
Depth	5.75 in (146.05 mm)

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA Type 1 indoor)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	64.02 in (162.6 cm)
Package 1 Width	22.01 in (55.9 cm)
Package 1 Length	5.75 in (14.6 cm)
Package 1 Weight	141.00 lb(US) (63.957 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes