



Main

Product or Component Type	Weathershield
Accessory / separate part category	Enclosure accessory

Complementary

Material	Gray painted steel
Mounting Mode	Bolt-on
Product destination	Transformer
Box number	20D 19D 21D
Type of Installation	Indoor/outdoor
Height	6.2 in (157.48 mm)
Width	29.5 in (749.30 mm)
Depth	3.125 in (79.38 mm)

Ordering and shipping details

Category	16270-LVGP PARTS
Discount Schedule	PE2
GTIN	785901357018
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.50 in (8.89 cm)
Package 1 Width	8.60 in (21.844 cm)
Package 1 Length	30.60 in (77.724 cm)
Package 1 Weight	7.14 lb(US) (3.239 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------