

CH366DS

Safety switch, heavy duty, fusible, 600A, 600 VAC/VDC, 3 poles, 500hp, NEMA 4, 4X, 5, 304 steel



Main

Product or Component Type	Single Throw Safety Switch
Disconnecter device type	Fusible disconnect
Number of poles	3
Electrical Connection	Lugs
Series name	Heavy duty

Complementary

Line Rated Current	600 A
Device Composition	None
Device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
Motor power hp	150 Hp at 480 V AC 50-60 Hz for 3 phase motors 400 Hp at 480 V AC 50-60 Hz for 3 phase motors 200 Hp at 600 V AC 50-60 Hz for 3 phase motors 500 Hp at 600 V AC 50-60 Hz for 3 phase motors 50 Hp at 250 V DC 50 hp at 600 V DC
AWG gauge	AWG 3/0...500 kcmil copper or aluminium
Tightening torque	375 lbf.in (42.37 N.m) (AWG 3/0...500 kcmil)
Height	46.25 in (1174.75 mm)
Width	26.25 in (666.75 mm)
Depth	10.13 in (257.30 mm)

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 4/4X stainless steel 304

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product