



Main

| | |
|----------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCKY |
| Product compatibility | XCKL XCKM XCKS |
| Associated head | ZCKD05 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return elastomer variable length, roller diameter 50 mm) |
| Type of approach | Lateral approach |

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | Without |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) standard environment |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) standard environment |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------|------------------------|
| Package 1 Weight | 0.09 lb(US) (0.041 kg) |
| Package 1 Height | 0.250 dm |
| Package 1 width | 1.000 dm |
| Package 1 Length | 1.000 dm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|