

## YA352N, Compression Terminal, 550 kcmil Cu, 2-Hole, 1/2" Stud, 1- 3/4" Spacing, Long Barrel

By Burndy  
Catalog # YA352N



550 kcmil CU, Two Hole, 1/2 Stud Size, 1-3/4 Hole Spacing, Long Barrel Internal Chamfer, Tin Plated, UL/CSA, 90°C, Up to 35kV, Color Code, Die Index.

### Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Long barrel length allows for an increased number of crimps increasing the mechanical strength of the connection
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- 2-Hole design prevents rotation

### Application

Wire Termination

### General

Catalog Number	YA352N
Color Code	Yellow
Connector Type	LONG BARREL
Die Index	21
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Long
Finish Type	Tin-Plated
Material	COPPER
Physical Attribute - Number of Holes	2
Plated	Y
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
Type	Long Barrel, Tin Plated
UPC	781810262184
UPC 12 Digit	7818102621844

### Dimensions

Dimension - B Length fraction	2-5/8 in
Dimension - B Length inch	2.63 in
Dimension - Bolt Hole Size inch	0.52 in
Dimension - Bolt Size fraction	1/2
Dimension - Bolt Size inch	0.5
Dimension - Hole Size fraction	1/2

Dimension - Hole Size inch	0.56
Dimension - Hole Size mm	14 mm
Dimension - L Length Overall mm	165 mm
Dimension - Length Overall inch	6.49 in
Dimension - N inch	0.63 in
Dimension - Outside Diameter inch	1.13 in
Dimension - Pad Width inch	1.65 in
Dimension - Strip Length inch	2-11/16
Dimension - Stud Size fraction	1/2
Dimension - Stud Size inch	1/2
Dimension - Z (inch)	0.64 in
Physical Attribute - Tongue Angle	Straight

### Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

### Conductor Related

Conductor - Copper DLO Size Range	N/A
Conductor - Copper Str Size	550 KCMIL
Conductor - Copper Str Size Range	550 kcmil
Conductor - Material	COPPER
Conductor Size	550 KCMIL
Conductor Type	CODE

### Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM

UL Listed Yes

**Logistics**

Carton Quantity 6  
Minimum Pack Quantity 6

**Product Assets**

Catalogs - BURNDY Master Catalog - Section C - Compression Connections  
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog  
Installation Manuals - Copper Code Long Terminals Tooling and Installation Instructions  
Interactive Catalog - BURNDY Full-Line Digital Catalog  
Sales Drawings - SD..031189-04  
Specifications - YA352N  
Video - HYDENT Compression Terminal Overview Video



A Hubbell brand