

CHU3613DSEI2J2WW

Safety switch, heavy duty, non fusible, 30A,
600 VAC/VDC, 3 poles, 30 hp, NEMA 4, 4X, 5,
304 stl, volt ind, interlock 2



Main

Range of product	Square D
Product or Component Type	Single Throw Safety Switch
Product destination	Wiring connection
Line Rated Current	30 A
NEMA degree of protection	NEMA 4/4X stainless steel 304
Maximum Horse Power Rating	5 Hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 10 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 Hp 480 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 20 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 Hp 600 V at DC for 1 phase conforming to NEC 240.6 30 Hp 600 V at DC for 3 phase conforming to NEC 430.52 5 Hp 250 V at 15 hp 250 V at
Disconnecter device type	Non-fusible disconnect
Maximum short-circuit current	10 kA
Device mounting	Surface
Number of poles	3
Phase	3 phase
Product Certifications	CSA
[Ue] rated operational voltage	600 V AC/DC
Wiring configuration	4-wire
AWG gauge	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper

Complementary

Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in ² (13.3 mm ²) (AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in ² (2.06...5.21 mm ²) (AWG 14...AWG 10)
Width	8.67 in (220.22 mm)
Height	14.93 in (379.22 mm)
Depth	5.11 in (129.79 mm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
