



Main

Product or Component Type	Elbow
Range	I-Line

Complementary

Rated Current	4000 A
Busbar Material	Aluminium busbar
Busbar Position	Edgewise
Integral Ground	50 percent capacity integral ground bus
Rated Operational Voltage	600 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
Length	11 in (279.40 mm)
Height	11 in (279.40 mm)

Ordering and shipping details

Category	20018-4000A AL FEEDER BU IP54 THERMAL
Discount Schedule	PE8
GTIN	00785901146995
Package weight(Lbs)	98.09 lb(US) (44.493 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------
