



## Main

|                           |   |
|---------------------------|---|
| Range of Product          | Harmony 9001SK  |
| Product or Component Type | Pilot light   |
| Device short name         | 9001SK  |
| Lens type                 | Fresnel plastic                                       |
| Light block supply        | Via integral transformer 220...240 V AC 50/60 Hz 6 V) |

## Complementary

|   |  |
|---|--|
| Bezel material                              | Plastic  |
| Mounting diameter                           | 1.18 in (30 mm)  |
| Shape of signaling unit head                | Round  |
| Cap/operator or lens colour                 | White  |
| Light source                                | incandescent   |
| Bulb base                                   | BA 9s  |
| [Us] rated supply voltage                   | 220...240 V AC 50/60 Hz  |
| Tightening torque                           | 7.08 lbf.in (0.8 N.m) EN/IEC 60947-1                                     |
| Shape of screw head                         | Cross slotted  |
| Connections - terminals                     | Screw clamp terminals, 1 x 0.22...2 x 1.5 mm <sup>2</sup> EN/IEC 60947-1 |
| [Ith] conventional free air thermal current | 10 A   |
| Short-circuit protection                    | 10 A cartridge fuse EN/IEC 60947-5-1                                     |
| [Ui] rated insulation voltage               | 250 V 2)EN/IEC 60947-1   |
| [Uimp] rated impulse withstand voltage      | 2.5 kV EN/IEC 60947-1  |
| Operating position                          | Any position   |
| CAD overall width                           | 2.13 in (54 mm)  |
| CAD overall height                          | 2.76 in (70 mm)  |
| CAD overall depth                           | 1.65 in (42 mm)  |
| Net Weight                                  | 0.40 lb(US) (0.181 kg)   |
| Device presentation                         | Complete product   |
| Lens type                                   | Fresnel  |
| [Us] rated supply voltage                   | 220...240 V  |
| Light block supply                          | Via integral transformer   |
| Supply frequency                            | 50...60 Hz   |
| Lens material                               | Polycarbonate  |
| Size  | 30 mm  |
| Light source                                | Incandescent bulb  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Electrical shock protection class     | Class II IEC 61140   |
| Protective treatment                  | TC   |
| IP degree of protection               | IP66 IEC 60529   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X   |
| Vibration resistance                  | 7 gn 2...500 Hz)IEC 60068-2-6  |
| Shock resistance                      | 50 gn IEC 60068-2-27   |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)   |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)   |
| Standards                             | JIS C8201-5-1<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14<br>UL 508<br>JIS C 852<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>JIS C8201-1 |
| Product Certifications                | UL 508[RETURN]NEMA   |

## Ordering and shipping details

|                   |                   |
|-------------------|-------------------|
| Category          | 21429-9001 SK,SKY |
| Discount Schedule | CS1               |
| GTIN              | 785901843771      |
| Returnability     | No                |
| Country of origin | MX                |

## Packing Units

|                              |                     |
|------------------------------|---------------------|
| Unit Type of Package 1       | PCE                 |
| Number of Units in Package 1 | 1                   |
| Package 1 Height             | 2.00 in (5.08 cm)   |
| Package 1 Width              | 2.00 in (5.08 cm)   |
| Package 1 Length             | 3.50 in (8.89 cm)   |
| Package 1 Weight             | 6.03 oz (171.004 g) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

---

|                     |  |
|---------------------|--|
| Circularity Profile | <a href="#">End Of Life Information</a>  |
| WEEE                | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

---

**Contractual warranty**

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---