

WOOD CONSTRUCTION CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (mm)	Tooth Grind	Part No.	10 Pack (Bulk)
5-3/8"	16	Framing	15°	0.063	15° ATB	48-40-0522	-
5-3/8"	36	Finish	15°	0.063	15° ATB	48-40-0524	-
5-1/2"	18	Framing	18°	0.063	15° ATB	48-40-0520	-
6-1/2"	24	Framing	18°	0.063	15° ATB	48-40-0620	48-41-0620
6-1/2"	40	Finish	15°	0.063	15° ATB	48-40-0622	-
7-1/4"	24	Framing	20°	0.063	12° ATB	-	48-41-0710
7-1/4"	24	Framing	18°	0.063	15° ATB	48-40-0720	48-41-0720
7-1/4"	24	Framing	20°	0.063	12° ATB	-	48-41-0713
7-1/4"	24	Framing	18°	0.063	15° ATB	-	48-41-0723
7-1/4"	40	Finish	15°	0.063	15° ATB	48-40-0726	48-41-0726
7-1/4"	60	Finish	15°	0.063	30° ATB	48-40-0730	48-41-0730
8-1/4"	24	Framing	18°	0.083	15° ATB	48-40-0820	-
8-1/4"	40	Finish	15°	0.083	15° ATB	48-40-0822	-
8-1/4"	60	Finish	12°	0.094	15° ATB	48-40-0826	-
8-1/2"	40	General Purpose	15°	0.094	10° ATB	48-40-0824	-
10"	24	Ripping	22°	0.094	15° ATB	48-40-1020	-
10"	40	General Purpose	15°	0.094	10° ATB	48-40-1024	-
10"	50	Combination	12°	0.094	15° + FTG ATB	48-40-1026	-
10"	60	Finish	12°	0.094	25° ATB	48-40-1028	-
10"	80	Finish	12°	0.094	25° ATB	48-40-1032	-
10"	40 & 60	General Purpose/Finish	15° & 12°	0.094 & 0.094	10° & 25° ATB	48-40-1036	-
10-1/4"	28	Framing	18°	0.102	15° ATB	48-40-1038	-
10-1/4"	40	Finish	12°	0.102	15° ATB	48-40-1040	-
12"	44	General Purpose	15°	0.118	10° ATB	48-40-1220	-
12"	60	Combination	12°	0.118	15° ATB	48-40-1222	-
12"	80	Finish	12°	0.118	25° ATB	48-40-1224	-
12"	100	Finish	12°	0.118	30° ATB	48-40-1228	-
12"	44 & 80	General Purpose/Finish	15° & 12°	0.118 & 0.118	10° & 25° ATB	48-40-1232	-

CIRCULAR SAW BLADES

PCD/FIBER CEMENT CIRCULAR SAW BLADES

OVERVIEW

MILWAUKEE® PCD/Fiber Cement Circular Saw Blades provide up to 75X longer life, increased accuracy and cooler cuts in fiber cement applications. The blades are designed utilizing Polycrystalline Diamond Teeth to extend cutting life in fiber cement material. The blades feature Laser Cut Vibration Slots to reduce wobble and warping. With an Anti-Friction Coating, the blades resist corrosion and gumming. MILWAUKEE's Circular Saw Blades are optimized for cordless and corded performance.



FEATURES

- Polycrystalline Diamond Teeth: Extend cutting life in fiber cement up to 75X longer
- Anti-Friction Coating: Provides cooler cuts
- Laser Cut Vibration Slots: Increase blade accuracy and prevents wobble and warping

PCD/FIBER CEMENT CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (mm)	Tooth Grind	Part No.
7-1/4"	4T	Fiber Cement	10°	0.071	ATB	48-40-7000
10"	6T	Fiber Cement	10°	0.079	ATB	48-40-7010
12"	8T	Fiber Cement	10°	0.087	ATB	48-40-7020

METAL CUTTING CIRCULAR SAW BLADES

OVERVIEW

MILWAUKEE® Metal Circular Saw Blades were specifically designed to exceed the expectations of contractors for blade life, cut quality, and speed in the most demanding metal cutting applications – without a lubricant. A hand-tensioned, hardened alloy steel body extends blade life and delivers the highest quality cuts available. Carbide Tipped teeth with Alternate Top Bevel grind shear through metal leaving burr-free, cool-to-touch cuts.



FEATURES

- Dry: No lubricant required, saving time and money with less mess
- Cool: No extreme heat buildup preserves blade life and allows handling the work piece immediately
- Clean: No burrs eliminates secondary operations, saving time and money

CIRCULAR SAW BLADES