

Product data sheet

Characteristics

8910DPA93V09

Contacteur, Definite Purpose, 90A, 3 pole, 50HP at 575VAC, 3 phase, 208/240VAC 60Hz 220VAC 50Hz coil, open



Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	90 A
Number of Poles	3P
Pole contact composition	3 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	7.5 Hp 115 V AC, 1 phase 20 Hp 230 V AC, 1 phase 30 Hp 230 V AC, 3 phase 50 Hp 460 V AC, 3 phase 50 hp 575 V AC, 3 phase
Locked rotor rated current	540 A 277 V AC 450 A 460 V AC 360 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	208...240 V AC 60 Hz 220 V AC 50 Hz
Phase	3 phase
Electrical Connection	Quick connect terminals Box lugs

Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------

Ordering and shipping details

Category	21349-8910 DPA 9_(90 AMP)
Discount Schedule	CP1B
GTIN	785901118404
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.00 in (15.24 cm)
Package 1 Width	5.50 in (13.97 cm)
Package 1 Length	7.00 in (17.78 cm)
Package 1 Weight	3.61 lb(US) (1.638 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------