

Clamps

- Use to secure wires, cables, pipes, tubing and fiber optics
- Ultraviolet black nylon clamps available for internal and external use
- Use with #10 mounting screw



| Description | Closed Diameter | Center to Center | Width | Thickness | Mounting Hole | UL Type | Plenum Approval | Qty./Bag | Part No. |
|----------------|-------------------|------------------|---------|-----------------|-----------------|---------|-----------------|----------|--------------|
| Natural Nylon | .125 in./3.18mm | .343 in./8.71mm | 3/8 in. | .050 in./1.27mm | .203 in./5.16mm | 21 | AH-2 | 100 | IT125CCL-C |
| Natural Nylon | .250 in./6.35mm | .421 in./10.69mm | 3/8 in. | .050 in./1.27mm | .203 in./5.16mm | | | 100 | IT250CCL-C |
| UV Black Nylon | | | | | | | | 100 | IT250CCL-C0 |
| Natural Nylon | .375 in./9.52mm | .500 in./12.70mm | 1/2 in. | .060 in./1.52mm | .203 in./5.16mm | | | 100 | IT375CCL2-C |
| UV Black Nylon | | | | | | | | 100 | IT375CCL2-C0 |
| Natural Nylon | .500 in./12.70mm | .553 in./14.05mm | 1/2 in. | .060 in./1.52mm | .203 in./5.16mm | | | 100 | IT500CCL2-C |
| Natural Nylon | .625 in./15.88mm | .625 in./15.88mm | 1/2 in. | .060 in./1.52mm | .203 in./5.16mm | | | 100 | IT625CCL2-C |
| Natural Nylon | .750 in./19.05mm | .699 in./17.75mm | 1/2 in. | .060 in./1.52mm | .203 in./5.16mm | | | 100 | IT750CCL2-C |
| Natural Nylon | 1.000 in./25.40mm | .825 in./20.96mm | 1/2 in. | .060 in./1.52mm | .203 in./5.16mm | | | 100 | IT1000CCL2-C |

Plenum Cable Ties

- UL Listed nylon 6/6 cable ties are suitable for use in Air Handling Spaces (Plenum) in accordance with Section 300-22(C) & (D) of the National Electrical Code and Rules 12-010 (3), (4) and (5) and 12-020 of the Canadian Electrical Code, Part 1



Standard Ties

| Description | Length | Width | Thickness | Max. Bundle | Tensile Strength | Mil-Spec Reference | UL Type | Plenum Approval | Qty./Bag | Part No. |
|----------------|----------------|-----------------|-----------------|-------------------|------------------|--------------------|---------|-----------------|----------|----------|
| Burgundy Nylon | 7.5 in./190mm | .178 in./4.52mm | .053 in./1.34mm | 1/16 - 1-7/8 in. | 50 lbs. | — | 21 | AH-2 | 100 | IT2S-C35 |
| Natural Nylon | | | | | | MS3367-1-9 | | | 100 | IT2S-C |
| Natural Nylon | | | | | | MS3367-1-0 | | | 1000 | IT2S-M |
| UV Black Nylon | | | | | | | | | 100 | IT2S-C0 |
| UV Black Nylon | | | | | | 1000 | | | IT2S-M0 | |
| Burgundy Nylon | 11.2 in./284mm | .178 in./4.52mm | .053 in./1.34mm | 1/16 - 3-1/16 in. | 50 lbs. | — | | | 100 | IT3S-C35 |
| Natural Nylon | | | | | | MS3367-7-9 | | | 100 | IT3S-C |
| Natural Nylon | | | | | | MS3367-7-0 | | | 500 | IT3S-D |
| UV Black Nylon | | | | | | | | | 100 | IT3S-C0 |
| UV Black Nylon | | | | | | | | | 500 | IT3S-D0 |
| Natural Nylon | 14.5 in./368mm | .178 in./4.52mm | .053 in./1.34mm | 1/16 - 4-1/8 in. | 50 lbs. | MS3367-2-9 | 100 | IT4S-C | | |
| Natural Nylon | | | | | | MS3367-2-0 | 500 | IT4S-D | | |
| UV Black Nylon | | | | | | | 100 | IT4S-C0 | | |
| UV Black Nylon | | | | | | | 500 | IT4S-D0 | | |

Mounting Ties

| Description | Length | Width | Strap Thickness | Max. Bundle | Tensile Strength | Screw Size | UL Type | Plenum Approval | Qty./Bag | Part No. |
|----------------|---------------|-----------------|-----------------|------------------|------------------|------------|---------|-----------------|----------|-----------|
| Natural Nylon | 8.1 in./206mm | .178 in./4.52mm | .053 in./1.35mm | 1/16 - 1-3/4 in. | 50 lbs. | No. 10 | 21 | AH-2 | 100 | IT2SMH-C |
| Natural Nylon | | | | | | | | | 1000 | IT2SMH-M |
| UV Black Nylon | | | | | | | | | 100 | IT2SMH-C0 |

