



Timer Controls: Digital/Electronic Controls

ET2725CP | 7-Day/365 Day Basic Plus Electronic Control



ET2725CP

7-DAY/365 DAY BASIC PLUS ELECTRONIC CONTROL

The ET2000 Series offers an easy-to-use interface, while still allowing to-the-minute scheduling capabilities for nearly any application. This series provides 50 holiday blocks with independent scheduling to ensure the loads are always in the proper ON/OFF state. This series also includes 96 ON/OFF events for even the most demanding schedules. The scheduling capabilities, configurable outputs, and a 100-hour backup without the need of batteries, make this series ideal for nearly any application.



Features & Applications

Features

- 100-hour supercapacitor eliminates the need for batteries
- Up to 96 set points or events
- Up to 50 holiday blocks with schedule capabilities
- Automatic input voltage selection from 120 to 277 VAC, 60 Hz
- Additional mode of operation turns the ON/OFF buttons into 2-hour overrides
- Configurable outputs allow the control of various voltages and applications
- Relays incorporate zero-crossing technology to extend the life of the control
- Non-volatile EEPROM memory protects programming indefinitely
- LED compatible
- USB port makes transferring and saving of schedules easy
- 2-year limited warranty

Applications

- Interior Lighting
- Exterior Lighting
- Electric Pumps
- Electric Motor Control
- Various Other Electrical Loads

Specifications

Minimum ON/OFF Times 1 min	Product Height (in) 10	Resistive (NO) 30 A, 120/240 VAC, 60 Hz
Maximum ON/OFF Times Indefinite	Product Height (mm) 254	Inductive (NO) 30 A, 120/240 VAC, 60 Hz
Minimum Pulse Time 2 sec	Product Width (in) 6.5	Magnetic Ballast (NO) 20 A, 120-277 VAC, 60 Hz
Maximum Pulse Time 2 sec	Product Width (mm) 165.1	Tungsten (NO) 5 A, 120-277 VAC, 60 Hz
Maximum ON/OFF Operations 96	Product Depth (in) 4	Motor (NO) 1 HP, 120 VAC, 60 Hz 2 HP, 240 VAC, 60 Hz
Setpoint Program Count 96	Product Depth (mm) 101.6	Switch Type 2x SPST, 1xDPST or Pulse
ON/OFF Operations 96	Wire Size Min #14 AWG	Maximum Power Consumption (W) 5 W
Operation Features Holiday	Wire Size Max #8 AWG	Operating Temperature Min (F) -40
Operation Mode 7-day	Wiring Option Terminals	Operating Temperature Max (F) 104
Daylight Savings Adjustment Automatic	Knockout Dimensions Bottom (2) combination 1/2" - 3/4"	Operating Temperature Min (°C) -40
	Knockout Dimensions Back/Side (1) combination 1/2" - 3/4"	
	Voltage Selection Type	

Backup Restoration

Time

30 Minutes

Backup Type

Supercapacitor

Backup Protection

Time

100 Hour

Enclosure Type

Indoor/Outdoor Type 3R
Plastic with See-Through
Door

Auto Voltage

Number of Circuits

2

Input Voltages

120-277 VAC, 60 Hz

Operating

Temperature Max

(°C)

40

Other Certifications and Compatibilities

LED

Warranty

2-Year limited

For California residents, click [here](#) for Proposition 65 Warning.

[Videos](#)