



Main

Range	PowerLogic
Product or Component Type	PT module

Complementary

Associated fuse rating	High voltage F1 - 315 mA High voltage F2 - 315 mA High voltage F3 - 315 mA Voltage F4 - 250 mA Voltage F5 - 250 mA Voltage F6 - 250 mA Voltage F7 - 250 mA
Input voltage	480 V +/- 10 %
Output voltage	120 V +/- 0.3 %
Type of Installation	Enclosed outdoor Indoor
Height	8.39 in (213 mm)
Width	13.54 in (344 mm)
Depth	2.13 in (54 mm)
Net Weight	12.50 lb(US) (5.67 kg)

Environment

Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
Relative humidity	5...90 % non-condensing
Operating altitude	9842.52 ft (3000 m)
Pollution degree	2

Ordering and shipping details

Category	09796-POWERLOGIC EM40/48 HARDWARE
Discount Schedule	PL1
Returnability	No
Country of origin	CA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.50 in (19.05 cm)
Package 1 Width	12.50 in (31.75 cm)
Package 1 Length	17.00 in (43.18 cm)
Package 1 Weight	3.50 lb(US) (1.588 kg)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
