

## EI500 Series

### Standard 7-Day Programmable Timers - 15 A

For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads.

#### Features

- 7-day programmable schedules with 14 ON/OFF events
- Automatic Daylight Saving Time (DST) adjustment
- Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- Single-pole circuit
- Incandescent/fluorescent/CFL/LED compatible
- Built-in rechargeable, non-serviceable battery backup
- Requires neutral connection
- Backlit LCD display

White	Ivory	Light Almond
EI500WC	EI500C	EI500LAC

Note: For use with standard decorator plate, not included.



White



Ivory



Light Almond



EI500WC



Ratings	
<b>Operating Voltage</b>	125 VAC, 60 Hz
<b>General Purpose</b>	15 A, 125 VAC, 60 Hz
<b>Resistive</b>	15 A, 125 VAC, 60 Hz
<b>Inductive Ballast (Fluorescent)</b>	1000 VA, 125 VAC, 60 Hz
<b>Electronic/LED Ballast</b>	500 VA, 125 VAC, 60 Hz
<b>Incandescent</b>	1000 W, 125 VAC, 60 Hz
<b>Motor</b>	¼ HP, 125 VAC, 60 Hz
<b>Operating Temperature</b>	32° F to 104° F (0° C to 40° C)
<b>Dimensions H x W x D</b>	4.125" X 1.75" X 1.4375" (104.8 mm x 44.5 mm x 36.5 mm)
<b>Warranty</b>	1-year limited

Note: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

## EJ600 Series

### Standard 7-Day Programmable Timers - 12 A

A 12 A rated timer that provides full 7-day programming capabilities with dusk-to-dawn functionality, ideal for use with medium to low power loads.

#### Features

- 7-day programmable schedules with 7 ON/OFF events
- Astronomic clock feature determines dawn and dusk times
- Automatic Daylight Saving Time (DST) adjustment
- Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- Single or 3-way switch compatible installation
- Incandescent/fluorescent/CFL/LED compatible
- Built-in rechargeable, non-serviceable battery backup
- Requires neutral connection

White	Light Almond
EJ600	EJ600A

Note: For use with standard decorator plate, not included.



White



Light Almond



EJ600



Ratings	
<b>Operating Voltage</b>	120 VAC, 60 Hz
<b>Resistive</b>	12 A, 120 VAC, 60 Hz
<b>Inductive Ballast</b>	500 VA, 120 VAC, 60 Hz
<b>Incandescent</b>	
<b>Single-Gang</b>	15 A, 120 VAC, 60 Hz
<b>Multi-Gang</b>	12 A, 120 VAC, 60 Hz
<b>Motor</b>	½ HP, 120 VAC, 60 Hz
<b>Operating Temperature</b>	32° F to 104° F (0° C to 40° C)
<b>Dimensions H x W x D</b>	4.125" X 1.75" X 1.4375" (104.8 mm x 44.5 mm x 36.5 mm)
<b>Warranty</b>	1-year limited

Note: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.