

Product data sheet

Characteristics

8538SCA24V02SY74

NEMA Combination Starter, Type S, 30A
fusible disconnect, Size 1, 27A, 10 HP at 600
VAC polyphase, 120 VAC coil, NEMA 12



Main

| | |
|----------------------|--------------------------|
| Product | Combination Starter |
| Type | S |
| Control Circuit Type | Separate control circuit |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 110 V AC 50 Hz 120 V AC 60 Hz |
| Starter Type | Non reversing |
| Number of Poles | 3P |
| Horsepower Rating | 10 Hp 460 V AC, 3 phase 10 hp 575 V AC, 3 phase |
| Maximum Voltage Rating | 600 V AC |
| Control Units | No control units |
| Pilot Light | No indicator |
| Auxiliary Contacts | Without |
| Thermal overload type | Melting alloy 3 |
| Disconnect Type | Fusible disconnect switch H, 30 A, electrical SPDT |
| NEMA size | 1 |

Environment

| | |
|----------------|---|
| Enclosure Type | NEMA 12 painted sheet steel with external reset |
|----------------|---|

Ordering and shipping details

| | |
|-------------------|------------------------------------|
| Category | 21213 - 8538,39 SC,SD(NOT S*R,T,W) |
| Discount Schedule | CP1 |
| GTIN | 785901503774 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 45.00 lb(US) (20.412 kg) |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Not compliant |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|