



## Main

|                           |                 |
|---------------------------|-----------------|
| Product or Component Type | Circuit breaker |
|---------------------------|-----------------|

## Complementary

|                                        |                                                                                                                                                                                                 |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Line Rated Current                     | 250 A                                                                                                                                                                                           |
| Number of Poles                        | 3P                                                                                                                                                                                              |
| Control type                           | Toggle                                                                                                                                                                                          |
| Breaking capacity code                 | L                                                                                                                                                                                               |
| Breaking capacity                      | 125 KA 240 V AC 50/60 Hz UL 489<br>100 KA 480 V AC 50/60 Hz UL 489<br>50 KA 600 V AC 50/60 Hz UL 489<br>20 KA 250 V DC UL 489<br>50 kA 500 V DC UL 489                                          |
| [Ue] rated operational voltage         | 600 V AC 50/60 Hz IEC 60947-3                                                                                                                                                                   |
| Network Frequency                      | 50/60 Hz                                                                                                                                                                                        |
| [Ics] rated service breaking capacity  | 125 KA 220/240 V AC 50/60 Hz IEC 60947-2<br>100 KA 380/440/415 V AC 50/60 Hz IEC 60947-2<br>50 KA 500/525 V AC 50/60 Hz IEC 60947-2<br>20 KA 250 V DC IEC 60947-2<br>20 kA 500 V DC IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 8 kV IEC 60947-2                                                                                                                                                                                |
| Trip unit technology                   | Thermal-magnetic                                                                                                                                                                                |
| Magnetic tripping current              | 2500 A                                                                                                                                                                                          |
| Magnetic hold current                  | 1250 A                                                                                                                                                                                          |
| Continuous current rating              | 80 %                                                                                                                                                                                            |
| [Ui] rated insulation voltage          | 750 V IEC 60947-2                                                                                                                                                                               |
| Protection Type                        | Overload protection<br>Short-circuit protection                                                                                                                                                 |
| Suitability for isolation              | Yes IEC 60947-2                                                                                                                                                                                 |
| Utilisation category                   | Category A                                                                                                                                                                                      |
| AWG gauge                              | AWG 3/0...350 kcmil aluminium/copper terminals                                                                                                                                                  |
| Local signalling                       | Switched off (OFF) 1 trip indicator green)                                                                                                                                                      |
| Mounting mode                          | Unit mount lug)                                                                                                                                                                                 |
| Mounting Support                       | Lug                                                                                                                                                                                             |
| Electrical connection                  | Lugs, line<br>Lugs, load                                                                                                                                                                        |
| Terminal identifier                    | AL250JD                                                                                                                                                                                         |
| Long time pick-up adjustment range     | 0.25...1 x In                                                                                                                                                                                   |
| Tightening torque                      | 221.27 lbf.in (25 N.m) 0.15...0.29 in <sup>2</sup> (95...185 mm <sup>2</sup> ) (AWG 3/0...350 kcmil)                                                                                            |

|                             |                                                                                                                                                           |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of slots             | 2 auxiliary switch OF plug-in)[RETURN]1 alarm switch SD plug-in)[RETURN]1 overcurrent trip switch SDE plug-in)[RETURN]1 voltage release MN or MX plug-in) |
| Power wire stripping length | 0.98 in (25 mm)                                                                                                                                           |
| Height                      | 7.52 in (191 mm)                                                                                                                                          |
| Width                       | 4.09 in (104 mm)                                                                                                                                          |
| Depth                       | 3.39 in (86 mm)                                                                                                                                           |
| Net Weight                  | 5.29 lb(US) (2.4 kg)                                                                                                                                      |
| Communication interface     | Modbus                                                                                                                                                    |
| Circuit breaker application | HACR rated                                                                                                                                                |

## Environment

|                                       |                                                                |
|---------------------------------------|----------------------------------------------------------------|
| Quality labels                        | CE                                                             |
| Standards                             | UL<br>CSA<br>NEMA<br>NOM-003-SCFI-2000<br>IEC 60947-2          |
| Product certifications                | UL[RETURN]CSA[RETURN]NOM                                       |
| IP degree of protection               | Front cover IP40                                               |
| Pollution degree                      | 3                                                              |
| Ambient Air Temperature for Operation | 28...158 °F (-2...70 °C)                                       |
| Ambient Air Temperature for Storage   | -58...185 °F (-50...85 °C)                                     |
| Operating altitude                    | < 6561.68 ft (2000 m) without derating<br>5000 m with derating |

## Ordering and shipping details

|                   |                                     |
|-------------------|-------------------------------------|
| Category          | 01120-HL,,JL UNIT MT BREAKER/SWITCH |
| Discount Schedule | DE2                                 |
| GTIN              | 785901683223                        |
| Returnability     | Yes                                 |
| Country of origin | MX                                  |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 5.71 in (14.5 cm)     |
| Package 1 Width              | 7.40 in (18.8 cm)     |
| Package 1 Length             | 8.82 in (22.4 cm)     |
| Package 1 Weight             | 4.76 lb(US) (2.16 kg) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                                                              |
| California proposition 65  | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                  |
| EU RoHS Directive          | Compliant with Exemptions                                                                                                                                                                                                                                                                                                          |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                                                             |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                                                                |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                                                                      |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                                                                                                                                                                                                                            |
| PVC free                   | Yes                                                                                                                                                                                                                                                                                                                                |

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

Approximate Dimensions

